

● YOUR
● SMART
● ENERGY



Stax - M30/M50

COMMERCIAL SERIES

POWER

30/50 kW

CAPACITY

60.25-216.9 kWh



- **Quick Installation:**
No battery rack or wiring needed — Plug and Play Solution.
- **Reliable Operation:**
AlphaESS BypassTech ensures continuity by isolating faults.
- **Maximize Battery Life:**
AI-driven diagnostics & calibration for SOC Consistency.
- **Easy Expansion:**
Plug-and-play batteries for seamless scaling.
- **200% PV input to boost profits**
- **IP66 for tough outdoor environments**
- **Heating Module integrated for low-temperature environments**

Alpha ESS Co., Ltd.

☎ +86 513 8060 6891
✉ info@alpha-ess.com
🌐 www.alphaess.com
📍 No. 1086, Bihua Road,
Nantong Hi-Tech Zone,
Jiangsu Province, China

Alpha ESS Italy S.r.l.

☎ +39 339 462 4288
✉ info@alphaess.it
🌐 www.alphaess.com
📍 Via Del Molinuzzo 83,
59100 Prato (PO), Italy

Alpha ESS Europe GmbH

☎ +49 610 3459 1601
✉ europe@alpha-ess.de
🌐 www.alphaess.de
📍 Horizon Tower 17.0G
Alfred-Herrhausen-Allee 3-5
65760 Eschborn, Germany

Alpha ESS UK Ltd.

☎ +44 0330 043 2610
✉ info@alpha-ess.com
📍 Drake house, Long street,
Dursley, GL11 4HH UK

Alpha ESS Australia Pty. Ltd.

☎ +61 02 9000 7676
✉ techsupport@alphaess.au
🌐 www.alphaess.com
📍 8/15-21 Gibbes Street,
Chatswood,
NSW 2067 Australia

Alpha ESS USA, Inc.

☎ +1 408 368 7828
✉ usa@alpha-ess.com
📍 Unit 5 2180 S Ivanhoe St,
Denver, CO 80222 USA

Alpha ESS International Pte. Ltd.

☎ +65 6513 1125 / +65 6513 1126
✉ Singapore@alpha-ess.com
📍 2 Corporation Road #01-06A
Corporation Place 618494
Singapore

Alpha ESS Korea Co., Ltd.

✉ info@alpha-ess.com
📍 2F, 19-4, Nohyeong 11-gil,
Jeju-si, Jeju-do, Republic
of Korea

Alpha ESS Benelux B.V.

✉ contact@alphaess.nl
🌐 www.alphaess.nl
📍 High Tech Campus 41, 5656AE
Eindhoven, Netherlands

Alpha ESS South Africa (Pty) Ltd.

✉ measservice@alpha-ess.com
📍 La Rocca Office Park, Block
B1 321 Main Road, Bryanston,
Johannesburg, 2191

Stax - M30/M50

Model	Stax - M30		Stax - M50	
System Specifications				
Nominal Output Power	30 kW		50 kW	
System Capacity	60.25 ~ 216.9 kWh			
Ingress Protection	IP66			
Battery Chemistry	LFP (LiFePO4)			
Warranty	5 Years Product Warranty, 10 Years Battery Warranty			
PV Side				
Max. Input Power	60 kW		100 kW	
Start-up Voltage	180 V			
MPPT Voltage Range	150 ~ 850 V			
Number of MPPTs	3		4	
Number of Strings per MPPT	6		8	
Max. Input Current	40 A * 3		40 A * 4	
Max. Short-circuit Current	60 A * 3		60 A * 4	
AC Data (Grid)				
Nominal Output Power	30 kW		50 KW	
Max. Output Apparent Power	30 kVA		50 kVA	
Nominal Grid Voltage	3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Nominal Grid Frequency	50 Hz / 60 Hz			
Max. Output Current	45.6 A		76 A	
Power Factor	< 0.99 (0.8 leading - 0.8 lagging)			
Max. THD of Current	< 3%			
AC Data (Backup)				
Nominal Output Power	30 kW		50 KW	
Max. Output Power	105% continuously ; 160% for 2s			
Back-up Swtich Time	< 10ms			
Nominal Output Frequency	3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Max. Output Current	45.6 A		76 A	
Max. THD of Voltage	< 2%			
AC Data (Generator)				
Max. Input Power	30 kW		50 KW	
Nominal Input Voltage	3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V			
Nominal Input Frequency	50 Hz / 60 Hz			
Nominal Input Current	45.6 A		76 A	
Efficiency				
Max. Efficiency	97.8%			
European Efficiency	97.4%			
Charging/Discharging Max. Efficiency	98.5%			
General Parameters				
Dimensions (W x D x H)	530 x 880 x 290 mm			
Weight	73 kg			
Operating Temperature Range	-25 ~ 60 °C			
Operating Humidity Range	0 ~ 95%			
Noise Emission	62 dB			
Corrosion Protection Class	C5			
Compliance	IEC 62109, IEC61000, VDE 4105, VDE 4110, TOR-R25, G99 G100, EN50549-1&-10, C10/11, NC RFG			
Battery Technical Specifications				
Module Model	M38314-S			
Module Capacity	12.05 kWh			
Depth of Discharge (DoD)	95% on grid ; 90% off grid			
Nominal Voltage	38.4 V			
Max. Charging/Discharging Current	157A*			
Operating Temperature Range	0 ~ 50 °C (Charging) ; -20 °C ~ 50 °C (Discharging)			
Cycle Life	8000 @ EOL 70% **			
Number of Battery Module	5 ~ 18***			
Dimensions (W x D x H)	550 x 615 x 250 mm			
Weight	90 kg			
Compliance	IEC 62619, IEC 62040, IEC 61000-6-1/-2/-3/-4, UL9540A			

* Max. charge/discharge current derating may occur with changes in temperature and SoC.

** Under specific test conditions.

*** Max. 12 battery modules per column, up to 2 columns.