

• YOUR  
• SMART  
• ENERGY



# SMILE-G3-T20

RESIDENTIAL SERIES

## POWER

20 kW

## CAPACITY

9.6 - 28.8 kWh with  
4.8 kWh Battery Module

19.2 - 57.6 kWh with  
9.6 kWh Battery Module



reddot design award 2022



GOOD DESIGN AWARD

- 3 MPPT for Higher PV Input
- Commercial Applications Compatibility
- Bypass Function for Series Battery
- Safer with Aerosols Inside the Battery
- Elegant Design

# SMILE-G3-T20



Model	SMILE-G3-T20
<b>System Specifications</b>	
Nominal Output Power	20 kW
Capacity Range	8.0 - 57.6 kWh
Battery Chemistry	LFP (LiFePO4)
Warranty	10 Years
<b>Inverter Technical Specifications</b>	
Model	SMILE-G3-T20-INV
Coupling	Hybrid
Max. PV Input Power	40 kW
Max. PV Input Current	18A/18 A/18 A
Max. PV Input Voltage	1 kV
MPPT Number / Max. Input Strings Number per MPPT	3/1
MPPT Voltage Range	200 - 850 V
Max. PV Short-Circuit Current	22.5 A / 22.5 A / 22.5 A
Max. Charging/Discharging Current	60 A
Max. Charging/Discharging Power	20 kW
Rated Frequency	50 / 60 Hz
Rated Voltage	220 V / 380 V, 230 V / 400 V
Phase	Three Phase
Rated Output Power (Grid Port)	20 kW
Rated Output Current (Grid Port)	29 A
Rated Output Power (Backup Port)	20 kW
Rated Input Power (on-grid)	25 kW
Backup	≤ 20 ms (EPS)
Communication	Ethernet / WiFi / Modbus / API
Relative Humidity	0 ~ 90% (No Condensation)
Dimensions (W x D x H)	610 x 250 x 610 mm
Weight	44 kg
IP Protection	IP65
Safety	IEC 62109-1/-2
EMC	IEC 61000-6-1/-3
Overvoltage Category	DC II
Noise	≤ 50 dB
Grid Regulation	VDE 4105, EN 50549-1, G99
Maximum / European Efficiency	98 % / 97.5 %

<b>Battery Technical Specifications</b>		
Module Model	SMILE-G3-BAT-4.8S	SMILE-G3-BAT-9.6S
Rated Capacity	4.8 kWh	9.6 kWh
Usable Capacity	4.56 kWh	9.3 kWh
Depth of Discharge (DoD)	95 % *	95 % *
Nominal Voltage	96 V	96 V
Max. Charging/Discharging Current	50 A	52.5 A
Charge rate	1 C	0.5 C
Operating Temperature Range	-20°C - 50°C **	-20°C - 50°C **
Battery Modules Quantity	2 - 6	2 - 6
IP Protection	IP65	IP65
Dimensions (W x D x H)	610 x 212.5 x 435 mm	610 x 210 x 634 mm
Weight	53 kg	81 kg
Fire-Fighting	Aerosol + Anti-explosion Valve	Aerosol + Anti-explosion Valve

\* Test condition: Max. 0.5C charge/discharge at 25±2°C.

\*\* Max. charge/discharge current derating may occur with changes in temperature and SoC.



Alpha ESS Co., Ltd.  
 ☎ +86 513 8060 6891  
 ✉ info@alpha-ess.com  
 🌐 www.alphaess.com  
 📍 No. 1086, Bihua Road,  
 Nantong Hi-Tech Zone,  
 Jiangsu Province, China

Alpha ESS Europe GmbH  
 ☎ +49 610 3459 1601  
 ✉ deutschland@alpha-ess.de  
 🌐 www.alphaess.de  
 📍 Horizon Tower 17.0G  
 Alfred-Herrhausen-Allee 3-5  
 65760 Eschborn, Germany

Alpha ESS Australia Pty. Ltd.  
 ☎ +61 02 9000 7676  
 ✉ techsupport@alphaess.au  
 🌐 www.alphaess.com  
 📍 8/15-21 Gibbes Street,  
 Chatswood,  
 NSW 2067 Australia

Alpha ESS International Pte. Ltd.  
 ☎ +65 6513 1125 / +65 6513 1126  
 ✉ Singapore@alpha-ess.com  
 📍 2 Corporation Road #01-06A  
 Corporation Place 618494  
 Singapore

Alpha ESS Benelux B.V.  
 ✉ contact@alphaess.nl  
 🌐 www.alphaess.nl  
 📍 High Tech Campus 41, 5656AE  
 Eindhoven, the Netherlands

Alpha ESS Italy S.r.l.  
 ☎ +39 339 462 4288  
 ✉ info@alphaess.it  
 🌐 www.alphaess.com  
 📍 Via Del Molinuzzo 83,  
 59100 Prato (PO), Italy

Alpha ESS UK Ltd.  
 ☎ +44 0330 043 2610  
 ✉ info@alpha-ess.co.uk  
 🌐 www.alpha-ess.co.uk  
 📍 Drake house, Long street, Dursley,  
 GL11 4HH United Kingdom

Alpha ESS USA, Inc.  
 ☎ +1 408 368 7828  
 ✉ usa@alpha-ess.com  
 📍 Unit 5 2180 S Ivanhoe St,  
 Denver, CO 80222 USA

Alpha ESS Korea Co., Ltd.  
 ✉ info@alpha-ess.com  
 📍 2F, 19-4, Nohyeong 11-gil,  
 Jeju-si, Jeju-do, Republic  
 of Korea

Alpha ESS South Africa (Pty.) Ltd.  
 ✉ measservice@alpha-ess.com  
 📍 La Rocca Office Park, Block  
 B1 321 Main Road, Bryanston,  
 Johannesburg, 2191