

YOUR
SMART
ENERGY



SMILE-G3-S3.6/S5

RESIDENTIAL SERIES

POWER

3.68 / 5 kW

CAPACITY

4.0 ~ 16.0 kWh with
4.0 kWh Battery Module

4.8 ~ 19.2 kWh with
4.8 kWh Battery Module

9.6 ~ 38.4 kWh with
9.6 kWh Battery Module



200% PV Input

All in One Design

MPPT Shadow Scanning

**Support Dual Power Supply
(Grid & Diesel Generator)**

No Additional High Voltage Box

150% Overload Capability for 30s

Support Multiple VPP Applications

Easy Installation and Maintenance

Bypass Function for Series Battery

SMILE-G3-S3.6/S5

Model	SMILE-G3-S3.6	SMILE-G3-S5	
System Specifications			
Nominal Output Power	3.68 kW	5 kW	
Capacity Range	4.0 ~ 38.4 kWh (95% DoD)		
Battery Chemistry	LFP (LiFePO4)		
Warranty	10 Years		

Inverter Technical Specifications			
Model	SMILE-G3-S3.6-INV	SMILE-G3-S5-INV	
Coupling	Hybrid	Hybrid	
Max. PV Input Power	7.36 kW	10 kW	
Max. PV Input Current	15 A / 15 A		
Max. PV Input Voltage	580 V		
MPPT Number / Max. Input Strings Number per MPPT	2 / 1		
MPPT Voltage Range	100 ~ 550 V		
Max. PV Short-Circuit Current	18.75 A / 18.75 A	24 A / 24 A	
Max. Charging/Discharging Current	60 A		
Max. Charging/Discharging Power	3.68 kW	5 kW	
Rated Frequency	50 / 60 Hz		
Rated Voltage	220 V / 230 V		
Phase	Single Phase		
Rated Output Current (Grid Port)	16 A	21.7 A	
Rated Output Current (Backup Port)	16 A	21.7 A	
Max. AC Input Power (On-Grid)*	7.36 kW	10 kW	
Backup	UPS		
Communication	Ethernet / WiFi / Modbus / API		
Relative Humidity	0 ~ 90% (No Condensation)		
Dimensions (W x D x H)	610 x 212x 366 mm		
Weight	19.5 kg		
IP Protection	IP65		
Safety	IEC 62109, IEC62040		
EMC	IEC 61000-6-1/-2/-3/-4		
Overvoltage Category	DC II		
Noise	≤35 dB		
Grid Regulation	VDE 4105, VDE 0126-01-01, EN 50549-1, CEI 0-21, RD 1699, G98/G99, AS 4777.2, NRS 097		
Maximum / European Efficiency	95.94 % / 94.71 %		

Battery Technical Specifications			
Module Model	SMILE-G3-BAT-4.0S	SMILE-G3-BAT-4.8S	
Rated Capacity	4.0 kWh	4.8 kWh	
Usable Capacity	3.8 kWh	4.56 kWh	
Depth of Discharge (DoD)	95 % *	95 % *	
Nominal Voltage	96 V	96 V	
Max. Charging/Discharging Current	42 A	50 A	
Operating Temperature Range	-10°C ~ 60 °C **	-20°C ~ 50°C **	
Battery Modules Quantity	1 ~ 4	1 ~ 4	
IP Protection	IP65	IP65	
Dimensions (W x D x H)	610 x 212.5 x 435 mm	610 x 212.5 x 435 mm	
Weight	42.5 kg	53 kg	
Fire-Fighting	N/A	Aerosol + Anti-explosion Valve	

* Test condition: Max. 0.5C charge/discharge at 25±2°C.

** Max. charge/discharge current derating may occur with changes in temperature and SoC.



Alpha ESS Co., Ltd.

+86 513 8060 6891
 info@alpha-ess.com
 www.alphaess.com
 No. 1086, BiHua Road,
 Nantong Hi-Tech Zone,
 Jiangsu Province, China

Alpha ESS Italy S.r.l.

+39 339 462 4288
 info@alphaess.it
 www.alphaess.com
 Via Del Molinuzzo 83,
 59100 Prato (PO), Italy

Alpha ESS Europe GmbH

+49 610 3459 1601
 europe@alpha-ess.de
 www.alphaess.de
 Horizon Tower 17.0G
 Alfred-Herrhausen-Allee 3-5
 65760 Eschborn, Germany

Alpha ESS UK Ltd.

+44 0330 043 2610
 info@alpha-ess.com
 Drake house, Long street,
 Dursley, GL11 4HH UK

Alpha ESS Australia Pty. Ltd.

+61 02 9000 7676
 techsupport@alphaess.au
 www.alphaess.com
 8/15-21 Gibbs Street,
 Chatswood,
 NSW 2067 Australia

Alpha ESS USA, Inc.

+1 408 368 7828
 usa@alpha-ess.com
 Unit 5 2180 S Ivanhoe St,
 Denver, CO 80222 USA

Alpha ESS International Pte. Ltd.

+65 6513 1125 / +65 6513 1126
 Singapore@alpha-ess.com
 2 Corporation Road #01-06A
 Corporation Place 618494
 Singapore

Alpha ESS Korea Co., Ltd.

info@alpha-ess.com
 2F, 19-4, Nohyeong 11-gil,
 Jeju-si, Jeju-do, Republic
 of Korea

Alpha ESS South Africa (Pty) Ltd.

measervice@alpha-ess.com
 La Rocca Office Park, Block
 B1 321 Main Road, Bryanston,
 Johannesburg, 2191